

**TECHNICAL DATA** 

# Fluke 324 True-RMS Clamp Meter with Temperature & Capacitance





## **Key features**

"It does everything a HVAC or Maintenance Tech would need. Out of 12 guys I work with 9 of them had the 324" - Thomas

- Rugged, reliable basic True-RMS clamp meter
- Measure AC current up to 400 A, AC/DC voltage to 600V
- Measure resistance up to  $4k\Omega$ , continuity detection  $\leq 30\Omega$
- Additions from 323 Clamp: Temperature, Capacitance, Backlight

## Product overview: Fluke 324 True-RMS Clamp Meter with Temperature & Capacitance

The Fluke 324 True-RMS Clamp Meter is a reliable, solid troubleshooting tool for commercial and residential electricians, featuring True-RMS measurements, a slim design for easy transport and use, and a large display for efficient troubleshooting. With the addition of Temperature and Capacitance, it has everything an HVAC technician could need.

## Troubleshoot problems safely and accurately

- CAT III 600 V, CAT IV 300 V safety rating
- Provides True RMS AC voltage and current for accurate measurements on non-linear signals



- Measures AC current up to 400 A
- Measures AC/DC voltage to 600V
- Measures resistance to  $4k\Omega$  with continuity detection  $\leq 30\Omega$
- Measures temperature from -10C to 400C
- Measures capacitance to 1000µF
- Backlight and hold function captures a reading on the display
- Comes with a two-year warranty and soft carrying case

### Fluke 320 Series Clamp Meters for electrical troubleshooting







Fluke 323 True-RMS Clamp Meter

Fluke 324 True-RMS Clamp Meter

Fluke 325 True-RMS Clamp Meter

|               | ruke szs muentis clamp meter | Trake set trac-tails clamp rieter | rune ses muentris clamp meter |
|---------------|------------------------------|-----------------------------------|-------------------------------|
| AC Current    | 400A                         | 40A / 400A                        | 40A / 400A                    |
| DC Current    |                              |                                   | 40A / 400A                    |
| AC/DC Voltage | 600V                         | 600V                              | 600V                          |
| Resistance    | 400Ω / 4kΩ                   | 400Ω / 4kΩ                        | 400Ω / 4kΩ / 40kΩ             |
| Continuity    | ≤ 70Ω                        | ≤ 30Ω                             | ≤ 30Ω                         |
| Capacitance   |                              | 100µF / 1000µF                    | 100µF / 1000µF                |
| Temperature   |                              | -10C to 400C                      | -10C to 400C                  |
| Backlight     |                              | Yes                               | Yes                           |
| Frequency     |                              |                                   | 5Hz to 500Hz                  |
| Min/Max       |                              |                                   | Yes                           |

### **Contents**:

- Fluke 324 True-RMS Clamp Meter
- TL75 Test Leads
- Type K Thermocouple
- Two AAA Batteries (Installed)
- Soft Case

## Specifications: Fluke 324 True-RMS Clamp Meter with Temperature & Capacitance

#### **Specifications**



|                     | Range             | 40.00 A / 400.0 A  |  |
|---------------------|-------------------|--|--|
| AC current          | Accuracy          | 1.5% ± 5 digits (45 Hz to 400 Hz)<br>Note: Add 2% for position sensitivity |  |
| D0 ourrent          | Range             | -  |  |
| DC current          | Accuracy          | -  |  |
| ACveltage           | Range             | 600.0 V  |  |
| AC voltage          | Accuracy          | 1.5% ± 5 digits  |  |
| DC voltage          | Range             | 600.0 V  |  |
| DC voltage          | Accuracy          | 1.0% ± 5 digits  |  |
| Desistance          | Range             | 400.0 Ω/ 4000 Ω  |  |
| Resistance          | Accuracy          | 1.0% ± 5 digits  |  |
| Continuity          |                   | ≤ 30 Ω   |  |
| Capacitance         |                   | 0 to 100.0 μF / 100μF to 1000 μF   |  |
| Frequency           |                   | -  |  |
| AC response         |                   | True-RMS   |  |
| Backlight           |                   | Yes  |  |
| Data hold           |                   | Yes  |  |
| Contact temperature |                   | -10.0°C to 400.0°C (14.0°F to 752.0°F)                                     |  |
| Min/Max             |                   | -  |  |
|                     | H x W x D (mm)    | 207 x 75 x 34  |  |
| Size                | Max wire diameter | 30 mm (600 MCM)  |  |
|                     | Weight            | 208 g  |  |
| Category rating     |                   | CAT III 600 V<br>CAT IV 300 V  |  |
| Warranty            |                   | Two-year   |  |



## **Ordering information**



### Fluke 324

Fluke 324 True-RMS Clamp Meter

Includes:

- Fluke 324 True-RMS Clamp Meter
- TL75 Test Leads
- Type K Thermocouple
- Two AAA Batteries (Installed)
- Soft Case

| Optional accessories                         | Description  |
|--|--|
| Fluke TL75 Hard Point™ Test Lead Set         | PVC-insulated, right-angle shrouded 4 mm (0.16 in) banana plugs  |
| Fluke TL175 TwistGuard™ Test Leads           | Simply twist to change the exposed probe tip length.   |
| Fluke TLK-225 SureGrip™ Master Accessory Set | Includes all the SureGrip™ leads and probes in a handy six-pocket, roll-up pouch, along with TL224 test leads. |
| Fluke insulated hand tools starter kit       | 8-piece kit has the most popular screwdrivers, pliers and cutters.   |



#### Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2023 Fluke Corporation. Specifications subject to change without notice. 03/2023

Modification of this document is not permitted without written permission from Fluke Corporation.